

Double-Layer Side Spray	Single-Layer Side Spray	70° Full Cone Spray	65° Flat Fan Spray
DL	SL	FC	DF
			




Performance Data 性能数据

型号	Thread size	Spray Pattern	Spray angle	Hole Dia.(mm)	FlowRate(L/min)
Model No.	螺纹尺寸	螺纹尺寸	喷雾角度	孔径 (mm)	3 bar pressure
DL	1/4"	Flat Fan	170°	4.0	3.0
SL		Flat Fan	170°	1.5	2.5
FC		Full Cone	70°	2.0	3.5
DF		Flat Fan	65°	2.8	3.2

Design Features 设计特点

- Uniform spray, long throw
- Anti-drip, instant shut-off
- Easy installation & removal
- 喷雾均匀，喷射距离长；广角扇形覆盖范围广
- 具有防滴漏功能，关水即停，能有效截断水流
- 易于安装及拆卸

Dimensions 尺寸

Sketch	Model No.	Material	Thread size	Length (mm)
简图	型号	材质	螺纹尺寸	长度
	DL	Plastic	1/4"	86
	SL			81
	FC			76
	DF			72

General Applications 一般应用

- Dairy cow humidification
- Farm & livestock cooling
- Cleaning
- 奶牛加湿
- 牧场，养殖场降温
- 清洗

Connector 连接器

Picture	Material	Thread size	Drilling hole dia. on pipe (mm)	Pipe outer Dia	
图片	材质	螺纹尺寸		inch	mm
	Plastic	1/4"	14mm	1"	32~35mm
				1 1/4"	38~43mm
				1 1/2"	44~51mm
				2"	54~60mm

Accessories 配件

